

MATERIAL

BESPOKE STONE + TILE

CREAM LIMESTONE

SOURCE: NORTH AMERICA

Cream is medium density, tight grain limestone with soft warm tones that make it highly versatile in design possibilities, from fireplaces to exterior cladding.

TECHNICAL DATA

ASTM 97 DENSITY	138.8 lbs/ft ³
ASTM 97 ABSORPTION	6.2%
ASTM C170 COMPRESSIVE STRENGTH	5,357 lbs/ft ² wet
ASTM C880 FLEXURAL STRENGTH	1,173 lbs/ft ² wet
ASTM 353 ABRASION RESISTANCE	LOW lbs/ft ³

AVAILABLE APPLICATIONS

ARCHITECTURAL ELEMENTS
MOLDING
TILE
MOSAICS

CONSIDERATIONS

VARIATION LOW
ACCEPTABLE TRAFFIC LOW

CARE AND MAINTENANCE

- High acid sensitivity is a property of limestone. Care must be taken in the presence of acidic foods and cleaning products.
- Low abrasion resistance is inherent in most limestone. Light scratching will occur with exposure to abrasives. A patina will result over time. Doormats are recommended when used as flooring.
- This limestone has a low to moderate absorption rate. It is recommended to seal this material prior to use to allow for additional time to “clean up” the spill, before it has time to result in a stain.

EXPLOREMATERIAL.COM

ATLANTA | AUSTIN | CHICAGO | COSTA MESA | DALLAS | DENVER | HOUSTON | SAN ANTONIO