

# MATERIAL

BESPOKE STONE + TILE

## PEWTER LIMESTONE

SOURCE: NORTH AMERICA

Pewter is a medium density, tight grain limestone with soft hues ranging from grey to brown. Its applications are limitless but is most often seen in outdoor or commercial applications.

### TECHNICAL DATA

ASTM 97 DENSITY	140.1 lbs/ft <sup>3</sup>
ASTM 97 ABSORPTION	5.6%
ASTM C170 COMPRESSIVE STRENGTH	3,970 lbs/ft <sup>2</sup> wet
ASTM C880 FLEXURAL STRENGTH	970 lbs/ft <sup>2</sup> wet
ASTM 353 ABRASION RESISTANCE	4.4 lbs/ft <sup>3</sup>

### AVAILABLE APPLICATIONS

ARCHITECTURAL ELEMENTS  
MOLDING  
TILE  
MOSAICS

### CONSIDERATIONS

VARIATION	LOW
ACCEPTABLE TRAFFIC	MED

### CARE AND MAINTENANCE

- High acid sensitivity is a property of limestone. Care must be taken in the presence of acidic foods and cleaning products.
- Low abrasion resistance is inherent in most limestone. Light scratching will occur with exposure to abrasives. A patina will result over time. Doormats are recommended when used as flooring.
- This limestone has a low to moderate absorption rate. It is recommended to seal this material prior to use to allow for additional time to “clean up” the spill, before it has time to result in a stain.

EXPLOREMATERIAL.COM

ATLANTA | AUSTIN | CHICAGO | COSTA MESA | DALLAS | DENVER | HOUSTON | SAN ANTONIO