

MATERIAL

BESPOKE STONE + TILE

RIVIERA BEIGE LIMESTONE

SOURCE: NORTH AMERICA

Riviera Beige is a highly versatile limestone with ivory and beige tones that make it ideal for any application, both interior and exterior. Its veining provides for stunning architectural and carved pieces.

TECHNICAL DATA

ASTM 97 DENSITY	120.1 lbs/ft ³
ASTM 97 ABSORPTION	12.52%
ASTM C170 COMPRESSIVE STRENGTH	3,040 lbs/ft ² wet
ASTM C880 FLEXURAL STRENGTH	680 lbs/ft ² wet
ASTM 353 ABRASION RESISTANCE	5.0 lbs/ft ³

AVAILABLE APPLICATIONS

ARCHITECTURAL ELEMENTS
MOLDING
TILE

CONSIDERATIONS

FREEZE / THAW	APPROVED
SALT WATER	APPROVED
VARIATION	MED
ACCEPTABLE TRAFFIC	LOW

CARE AND MAINTENANCE

- High acid sensitivity is a property of limestone. Care must be taken in the presence of acidic foods and cleaning products.
- Low abrasion resistance is inherent in most limestone. Light scratching will occur with exposure to abrasives. A patina will result over time. Doormats are recommended when used as flooring.
- This limestone has a low to moderate absorption rate. It is recommended to seal this material prior to use to allow for additional time to “clean up” the spill, before it has time to result in a stain.

EXPLOREMATERIAL.COM

ATLANTA | AUSTIN | CHICAGO | COSTA MESA | DALLAS | DENVER | HOUSTON | SAN ANTONIO