

MATERIAL

BESPOKE STONE + TILE



SIENNA LIMESTONE

SOURCE: NORTH AMERICA

Sienna is a medium density limestone with ivory to beige tones that make it highly versatile in design possibilities. It is available in a range of applications and finishes.

TECHNICAL DATA

ASTM 97 DENSITY	148.9 lbs/ft ³
ASTM 97 ABSORPTION	2.85%
ASTM C170 COMPRESSIVE STRENGTH	6,890 lbs/ft ² wet
ASTM C880 FLEXURAL STRENGTH	830 lbs/ft ² wet
ASTM 353 ABRASION RESISTANCE	15.9 lbs/ft ³

AVAILABLE APPLICATIONS

ARCHITECTURAL ELEMENTS
MOLDING
TILE
MOSAICS

CONSIDERATIONS

VARIATION	LOW
ACCEPTABLE TRAFFIC	MEDIUM

CARE AND MAINTENANCE

- High acid sensitivity is a property of travertine. Care must be taken in the presence of acidic foods and cleaning products.
- Low abrasion resistance is inherent in most travertine. Light scratching will occur with exposure to abrasives. A patina will result over time. Doormats are recommended when used as flooring.
- This travertine has a low to moderate absorption rate. It is recommended to seal this material prior to use to allow for additional time to “clean up” the spill, before it has time to result in a stain.

EXPLOREMATERIAL.COM

ATLANTA | AUSTIN | CHICAGO | COSTA MESA | DALLAS | DENVER | HOUSTON | SAN ANTONIO