

MATERIAL

BESPOKE STONE + TILE



BRECCIA FIORE MARBLE

SOURCE: NORTH AMERICA

A highly versatile marble with a medium color range and warm red-pink hues, Breccia Fiore will provide the pop of color your project needs.

TECHNICAL DATA

| | |
|--------------------------------|-------------------------|
| ASTM 97 DENSITY | 2700 kgs/m ³ |
| ASTM 97 ABSORPTION | 1.99% |
| ASTM C170 COMPRESSIVE STRENGTH | 814 kgs/cm ² |
| ASTM C880 FLEXURAL STRENGTH | --- kgs/cm ² |
| ASTM 353 ABRASION RESISTANCE | 0.68 mm |

AVAILABLE APPLICATIONS

ARCHITECTURAL ELEMENTS
MOLDING
TILE
MOSAICS

CONSIDERATIONS

| | |
|--------------------|----------|
| FREEZE / THAW | APPROVED |
| SALT WATER | APPROVED |
| VARIATION | HIGH |
| ACCEPTABLE TRAFFIC | HIGH |

CARE AND MAINTENANCE

- High acid sensitivity is a property of marble. Care must be taken in the presence of acidic foods and cleaning products.
- Low abrasion resistance is inherent in most marbles. Light scratching will occur with exposure to abrasives. A patina will result over time. Doormats are recommended when used as flooring.
- This marble has a low to moderate absorption rate. It is recommended to seal this material prior to use to allow for additional time to “clean up” the spill, before it has time to result in a stain.

EXPLOREMATERIAL.COM

ATLANTA | AUSTIN | CHICAGO | COSTA MESA | DALLAS | DENVER | HOUSTON | SAN ANTONIO