

MATERIAL

BESPOKE STONE + TILE



CARRARA MARBLE

SOURCE: ITALY

The original, and most sought-after white and grey Italian marble, Carrara has a medium color range. The classic soft veining is seen in structures and carvings all over the world. For when the best is the only acceptable option.

TECHNICAL DATA

ASTM 97 DENSITY	169.7 lbs/ft ³
ASTM 97 ABSORPTION	.06%
ASTM C170 COMPRESSIVE STRENGTH	11,340 lbs/ft ² wet
ASTM C880 FLEXURAL STRENGTH	240 lbs/ft ² wet
ASTM 353 ABRASION RESISTANCE	--- lbs/ft ³

AVAILABLE APPLICATIONS

ARCHITECTURAL ELEMENTS
MOLDING
TILE
MOSAICS

CONSIDERATIONS

VARIATION	LOW
ACCEPTABLE TRAFFIC	HIGH

CARE AND MAINTENANCE

- High acid sensitivity is a property of marble. Care must be taken in the presence of acidic foods and cleaning products.
- Low abrasion resistance is inherent in most marbles. Light scratching will occur with exposure to abrasives. A patina will result over time. Doormats are recommended when used as flooring.
- This marble has a low to moderate absorption rate. It is recommended to seal this material prior to use to allow for additional time to “clean up” the spill, before it has time to result in a stain.

EXPLOREMATERIAL.COM

ATLANTA | AUSTIN | CHICAGO | COSTA MESA | DALLAS | DENVER | HOUSTON | SAN ANTONIO