


MATERIAL

BESPOKE STONE + TILE



MONTCLAIR MARBLE

SOURCE: NORTH AMERICA

Montclair is one of the oldest quarried marbles in the U.S. With soft green/gray veins, medium color range, and wide variety of available finishes, this stone is highly versatile and brings a feeling of prestige to any project.

TECHNICAL DATA

ASTM 97 DENSITY	169.4 lbs/ft ³
ASTM 97 ABSORPTION	0.1%
ASTM C170 COMPRESSIVE STRENGTH	10,090 lbs/ft ² wet
ASTM C880 FLEXURAL STRENGTH	1,410 lbs/ft ² wet
ASTM 353 ABRASION RESISTANCE	16.1 lbs/ft ³

AVAILABLE APPLICATIONS

ARCHITECTURAL ELEMENTS
MOLDING
TILE
MOSAICS

CONSIDERATIONS

FREEZE / THAW	APPROVED
SALT WATER	APPROVED
VARIATION	MED
ACCEPTABLE TRAFFIC	HIGH

CARE AND MAINTENANCE

- High acid sensitivity is a property of marble. Care must be taken in the presence of acidic foods and cleaning products.
- Low abrasion resistance is inherent in most marbles. Light scratching will occur with exposure to abrasives. A patina will result over time. Doormats are recommended when used as flooring.
- This marble has a low to moderate absorption rate. It is recommended to seal this material prior to use to allow for additional time to “clean up” the spill, before it has time to result in a stain.

EXPLOREMATERIAL.COM

ATLANTA | AUSTIN | CHICAGO | COSTA MESA | DALLAS | DENVER | HOUSTON | SAN ANTONIO