

MATERIAL

BESPOKE STONE + TILE

PEARL MARBLE

SOURCE: NORTH AMERICA

Pearl is a very light neutral colored marble with tiny shell-like structural movement. Its minimal color range and wide variety of finishes available, make this stone highly versatile in interior and exterior applications.

TECHNICAL DATA

ASTM 97 DENSITY	163.7 lbs/ft ³
ASTM 97 ABSORPTION	0.49%
ASTM C170 COMPRESSIVE STRENGTH	13,880 lbs/ft ² wet
ASTM C880 FLEXURAL STRENGTH	1,890 lbs/ft ² wet
ASTM 353 ABRASION RESISTANCE	15.7 lbs/ft ³

AVAILABLE APPLICATIONS

ARCHITECTURAL ELEMENTS
MOLDING
TILE
MOSAICS

CONSIDERATIONS

VARIATION	LOW
ACCEPTABLE TRAFFIC	HIGH

CARE AND MAINTENANCE

- High acid sensitivity is a property of marble. Care must be taken in the presence of acidic foods and cleaning products.
- Low abrasion resistance is inherent in most marbles. Light scratching will occur with exposure to abrasives. A patina will result over time. Doormats are recommended when used as flooring.
- This marble has a low to moderate absorption rate. It is recommended to seal this material prior to use to allow for additional time to “clean up” the spill, before it has time to result in a stain.

EXPLOREMATERIAL.COM

ATLANTA | AUSTIN | CHICAGO | COSTA MESA | DALLAS | DENVER | HOUSTON | SAN ANTONIO